

FIREFIGHTER SYSTEM EN 81-72

IPX3 landing and car operating panels for firefighters system.

MAIN FEATURES:

- ✓ Types: 2 mm thick stainless/steel Italia faceplates;
- ✓ Fixing: by visible screw;
- ✓ Finishes: scotch brite or polished steel, satin or polished gold pvd, polished blu;
- ✓ IPX3 back protection box;
- ✓ IPX3 display, buttons and accessories;
- ✓ Handfree terminal in the car, machine room and on the landing access floor VVFF IPX3;
- ✓ Electronic components operating between 0° C and 65° C;
- ✓ Customisable sizes on request;



COP:

- Cop 250x1000x2 mm
- The handsfree terminal in the car
- key switch 2 positions 1 pull-out IPX3
- 20 x 20 mm pictogram next to firefighter access floor button
- IRIS 7" ,tft display 7" with anti-vandal kit;
- Push buttoni: ERCOLE, EN 81-71 class 2 –
ACHILLE, EN 81-71 class 1
- Emergency light: EL LINE



LOP FIREFIGHTER ACCESS:

- Lop 130 x 450 x 2 mm
- VVFF pictogram 100 mm x 100 mm
- Triangular key for firefighters EN 81-20 – EN 81-72
- Hands-free Master Device



LOP MACHINE ROOM:

- Lop 130x300x2mm
- Push Button: ERCOLE, EN 81-71 clas 2 –
ACHILLE, EN 81-71 class 1
- Hands-free floor device;



LOP STANDARD:

- Lop 130x200x2 mm;
- Push Button: ERCOLE, EN 81-71 class 2 - ACHILLE, EN 81-71 class 1



LIP:

- Lip 300X130x2 mm
- IRIS 4.3", tft display 4.3" with antivandal kit



OPTIONALS:

- Lop with push button and Display (TFT 4.3") 130 x 365 x 2 mm;
- IRIS 4.3, tft 4.3" display (vertical mounting) with antivandal kit
- Push button: Ercole, EN 81-71 class 2
ACHILLE, en 81-71 class 1 o 2

- Lop push button, Display and landing hand-free 130 x 590 x 2 mm
in compliance with D.M. 15/09/2005.



FOCUS:

ERCOLE – VANDAL-RESISTANT BUTTON CLASS 2 - WATER PROOF



- Body: vandal proof zamak push button in compliance to UNI EN 81-71 class 2;
- Bezels and pressel colour: chrome and gold;
- Pressel: damage free plastic with stainless steel AISI 304 or gold/black pvd coated finishes;
- Contacts: 1 micro switch or 2 micro switches.
- Wiring: PIN or pre-wired connectors (AMP or JSP)
- Illumination: Led 12V or 24V DC 30mA.
- Degree of protection: IP54
- Finishes: blasted stainless steel, gold bead blasted, black bead blasted.

IRIS 7" with Vandal Proof Kit



- 7 "Car high resolution position indicator;
- Glass: layered:
- Mounting: flush with welded studs

IRIS 4.3" CON KIT ANTIVANDALO



- 4.3" Car high resolution position indicator;
- Glass: layered:
- Mounting: horizontal or vertical with flush with welded studs

IPX3 BOX



- Entire box welded and sheathed for water resistance. Box degree of protection IP54.
- Depth 55mm

PICTOGRAM 20X20 MM ON THE LANDING FOR FIREFIGHTERS ACCESS (EN 81-20)



Triangular key for firefighters EN 81-20 – EN 81-72



HANDS-FREE TERMINAL IPX3

“intercom system”/two way speech device.



- **5HV-028 – INTERCOM SPEAKER UNIT**
Two-way communication (full-duplex)
Connection: 2 wires

- **5HV-155 – MASTER POWERCOMM FOR LANDING FIREFIGHTER ACCESS**
Contact for connecting an external activation key
Integrated speakerphone with trimmer for adjusting speaker volume and microphone sensitivity

- **5HV-151 – Push-to-talk floor terminal (machine room)**
Integrated hands-free
Power supply: directly supplied by the Master Powercomm terminal by means of connection bus
Contact for connecting an external activation key