



COMBI UPS

Auto-Dialer with battery management and din bar support for control panel installation.

MAIN FEATURES

- Buffer battery management 12V and efficiency test.
- Technical alarms management: power supply presence, low and/or inefficient battery.
- PSTN line input.
- 2 outputs relay enabled by remote or alarm event.
- Protocols Management for call-center (ex. Ademco Contact ID, P100).
- Simplified wiring system for speaker modules (Speakerlift) 2 wires.
- GSM line input with GSM300 device (optional).
- Programming by telephone keypad; locally and remotely.
- Programming via graphic display DISP903.
- Programming via Vegacom APP (only if there is GSM300)
- Programming via Managerlift (Vega Cloud).
- Memory capacity up to 10 phone numbers.
- 32 customizable messages divided into 4 languages.
- Inductive loop facility for the hard-of-hearing.
- 4 types of inputs: alarm input, alarm filter input, technical alarm input and reset alarm input.
- Sent and acknowledged alarm signals.

BENEFITS



BATTERY LEVEL CONTROL



SIMPLIFIED WIRING SYSTEM

SIZE

111x92x70 mm

TECHNICAL DATA

Input power supply: from 9V to 24V DC and AC.

Output power supply: 12V DC 500mA.

Inputs: 4x opto isolator 5-50V 50mA.

Outputs: 2x Relay, 2x Open Collectors.