



Contact à clé circulaire /  
Round key selector



Contact à clé carré /  
Squared key selector

## KL-KEY

Contact à clé lumineux.  
Illuminated key selector.



### FONCTIONS PRINCIPALES

- Structure: Bloc clé inséré sur corps en polycarbonate avec couronne qui peut être éclairée.
- Colletteres: ABS galvanisés (or ou chrome), disponible dans la version RONDE et CARREE.
- Partie frontale: bague en acier et bloc clé.
- Montage: le bouton est inséré de front dans un trou de diamètre 32,2 à l'aide d'une bague filetée.
- Épaisseur plaque: de 0,7 mm à 3 mm.
- Modèles disponibles:
  - K#2P1E, 2 Positions, 1 extraction;
  - K#2P2E, 2 Positions, 2 extractions;
  - K#1P1E, avec retour à ressort.
- Câblage: À fils.
- Alimentation couronne: (4XLED) 12 o 24 VDC I=20mA.
- Protection: IP51.
- En option: contact à clé sur base VENUS XL.

### MAIN FEATURES

- Body: Key block integrated in polycarbonate body with illuminated halo.
- Bezel: metallized ABS (gold or chrome); it is available in the ROUND and SQUARE version.
- Front part: Stainless Steel ring and key block.
- Mounting: it is put into the 32,2 cutout from the front and fixed by threaded ring.
- Faceplate thickness: 0,7 to 3mm.
- Available items:
  - K#2P1E (2 position/1 extraction);
  - K#2P2E (2 positions/2 extractions);
  - K#1P1E (with spring return).
- Wiring: by wires.
- Halo voltage: (4XLED) 12 or 24 VDC I=20mA
- Degree of protection: IP51.
- Optional: key block for VENUS XL model